


SAFS 22522 x 3.13/16 T



SAFS 22522 x 3.13/16 T Bearing dimensions and specification in SKF catalogue:

H	244.475 mm
L	419.1 mm
S	4.763 mm
h	45.244 mm
A1	120.65 mm
A2	231.775 mm
Ca	62.89 mm
Da	200 mm
H1	125.425 mm
H2	52.388 mm

SKF SAFS 22522 x 3.13/16 T Split Pillow Blocks Bearing Data Sheet:

J1	69.85 mm
N1	22.225 mm
PG	1/4 NPT
Pa	17.3 kN
R1	67.866 mm
R2	31.75 mm
RG	3/8 NPT
ba	50.006 mm
da	96.838 mm
J max.	368.3 mm
J min.	320.675 mm

Housing	SAFS 522
Cap bolt	5/8-11 UNC
Eye bolt	2 x 3/8-16 UNC
P60°;	178 kN
P90°;	107 kN
P120°;	66.7 kN
P150°;	59.6 kN
P180°;	72.5 kN
Taconite seal	TER 107
Stabilizing ring	SR-22-19
Mass pillow block	52.2 kg
Cap bolt, SAE grade	8
End plug (suffix Y)	EPR 13
Initial grease fill	232.47 g
Max. speed for Taconite seal	775 r/min
Appropriate attachment bolt size G	0.75 in
Cap bolt recommended tightening torque	298.3 N·m