


SAW 23538 T



SAW 23538 T Bearing dimensions and specification in SKF catalogue:

H	401.637 mm
L	711.2 mm
S	4.763 mm
h	63.5 mm
A1	190.5 mm
A2	339.725 mm
Ca	129.819 mm
Da	339.999 mm
H1	200.025 mm
H2	79.375 mm

SKF SAW 23538 T Split Pillow Blocks Bearing Data Sheet:

J1	114.3 mm
N1	34.925 mm
PG	1/4 NPT
Pa	68.5 kN
R1	120.65 mm
R2	42.069 mm
RG	1 NPT
ba	92.869 mm
da	176.213 mm
J max.	619.125 mm
J min.	549.275 mm
Housing	SAW 538

Cap bolt	4 x 7/8-9 UNC
Eye bolt	2 x 3/8-16 UNC
P60°	290 kN
P90°	173 kN
P120°	107 kN
P150°	94.3 kN
P180°	113 kN
Taconite seal	TER 155
Stabilizing ring	SR-38-32
Mass pillow block	172 kg
Cap bolt, SAE grade	5
End plug (suffix Y)	EPR 21
Initial grease fill	1672.65 g
Max. speed for Taconite seal	440 r/min
Appropriate attachment bolt size G	1.25 in
Cap bolt recommended tightening torque	271.2 N·m